



REVISIONS			DOC. NO. SPC-F004 * Effective: 7/8/02 * DCP No: 1398					
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
430	A	RELEASED	JWM	11/20/02	HO	11/25/02	DJC	12/6/02



FEATURES:

- Over-current protection: Automatically shuts off current flow when maximum output is exceeded
- Overload Indicator: Illuminates when over-current protection circuit is engaged
- Multi-terminal output: One set of large output current terminals (30A Max), two sets of small output terminals (6A Max) and one cigarette lighter socket (10A Max)

SPECIFICATIONS:

- Input: 117 VAC, 50/60 Hz
- Output Voltage: 1 ~ 15 VDC (Variable)
- Output Current: 40 Amps, 2 minutes on - 2 minutes off
32 Amps continuous use
- Voltage Fluctuation: Less than 1% at rated output
- Ripple Voltage: Less than 3mV at rated output
- Protection Circuit: Automatically engages at 42 Amps
- Dimensions: 9½"(W) x 4¾"(H) x 10⅝"(L)
- Weight: 19 Lbs.

SPC-F004.DWG

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	DRAWN BY:	DATE:	DRAWING TITLE:					
	Jeff McVicker	11/20/02	Regulated DC Power Supply					
	CHECKED BY:	DATE:	SIZE	DWG. NO.	ELECTRONIC FILE		REV	
	Hisham Odish	11/25/02	A	72-6180A	50N1362.dwg		A	
APPROVED BY:	DATE:	SCALE: NTS		U.O.M.: INCHES [mm]		SHEET: 1 OF 1		
Daniel Carey	12/6/02							

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY. DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.