



[Features](#)

[Specs](#)

Digital Sampling Oscilloscope

11801C

This product is discontinued.

View [alternative products](#).

Check [product support](#) status.

Features

11801C

- DC To 50 Ghz Bandwidth
- 7 Ps Rise Time
- Eight Channels, Expandable to 136 (with SM-11 multi-channel units)
- High Resolution and Measurement Repeatability
- 10 Femtosecond Sampling Interval (0.01 ps)
- Modular Architecture
- Dual Timebase Allows Multiple Windows
- FFT
- Predefined Telecom Masks
- True Dual-Step Differential TDR
- Fully Automatic Jitter and Noise Measurements
- Automatic Statistical Measurements, Histograms and Mask Testing
- Automatic Pulse Measurements with Statistics
- Comprehensive Waveform Processing
- Complete Programmability for ATE Applications
- Color Display with Color Grading

Applications

- Semiconductor Test
- TDR Characterization
- High Speed Digital
- Data Communication

The 11801C Digital Sampling Oscilloscope

The 11801C Digital Sampling Oscilloscope offers the widest range of on-board measurement and waveform processing capabilities of any multi-Gigahertz scope. With excellent measurement repeatability, exceptional vertical resolution and fast display update rate, the 11801C is a powerful measurement tool for semiconductor testing, TDR characterization of circuit boards, IC packages and cables, and high speed digital data communications.

Modularity Meets Your Needs Now and in the Future

The modular microprocessor-based architecture of the 11801C not only allows you to select the right configuration for your application, but also allows expandability to meet your future measurement needs. The 11801C accepts up to 4 dual-channel

sampling heads and can be expanded through the SM-11 Multi-Channel Units to 136 channels. There are currently nine sampling heads to choose from:

SD-14 3 GHz high impedance (100 kilohm/0.475 pF) dual-channel probe sampler

SD-20 20 GHz single-channel loop-through head

SD-22 12.5 GHz dual-channel low noise head

SD-24 20 GHz dual-channel TDR/sampling head

SD-26 20 GHz dual-channel sampling head

SD-32 50 GHz, single-channel sampling head

SD-42 6.4 GHz O/E converter (55 ps optical pulse response FWHM)

SD-44 15 GHz O/E converter

SD-51 20 GHz trigger head

 [Top of Page](#)

[Features](#)

[Specs](#)



Tektronix Measurement products are manufactured in ISO registered facilities.



49A-10733-3p112, 06/1997, 09/01/1999

[Have an Account Manager Contact Me](#)

[Request a Demo](#)

[Email This Page](#)

[Printable Page](#)

[URL for Favorites](#)

Tektronix Site

[Home](#) | [Products](#) | [Support](#) | [Buy](#) | [Contact Us](#) | [Investors](#) | [Careers](#) | [International](#) | [myTek](#)

[Sitemap](#) | [© Copyright Tektronix, Inc.](#) | [Privacy Statement](#)