

Optical Communications Home

Product Portfolio

[Selection Guide](#)
[Accessories](#)
[Find by Application](#)
[Request a Catalog](#)
[Product Finder](#)

Resources

[Technical Information](#)
[Manuals](#)
[FAQs](#)
[Software & Drivers](#)
[Service & Support](#)
[E-Newsletters](#)

What's New

[Promotions](#)
[News](#)
[Events](#)

[Features](#)
[> Specs](#)

Communications Signal Analyzer

CSA8000

This product is discontinued.

View [alternative products](#).

Check [product support](#) status.

Characteristics

Signal Acquisition

Acquisition Modes - Sample (normal), envelope and average.

Number of Sampling Modules Accommodated - Up to four, dual-channel electrical and two, single-channel optical sampling modules.

Number of Simultaneously Acquired Inputs - Eight channels maximum (eight electrical or two optical and six electrical).

Vertical Systems

Rise Time/Bandwidth - Determined by the sampling modules used.

Vertical Resolution - 14 bits over the sampling modules' dynamic range.

Horizontal System

Main and Magnification View Timebases - 1 ps/div to 5 ms/div in 1-2-5 sequence or 1 ps increments.

Time Interval Accuracy

Horizontal sensitivity < 21 ps: 1 ps + 1% of interval.

Horizontal sensitivity \geq 21 ps:

8 ps + 0.1% of interval (short-term optimized mode).

8 ps + 0.01% of interval (locked to 10 MHz mode).

Horizontal Deskew Range: -500 ps to +100 ns on any individual channel in 1 ps increments.

Record Length - 20, 50, 100, 500, 1,000, 2,000, 4,000 samples.

Magnification Views - In addition to the main timebase, the CSA8000 supports two magnification views. These magnifications are independently acquired using separate timebase settings.

Maximum Trigger Rate - 200 kHz.

Trigger System

Trigger Sources -

External direct trigger.

External pre-scaled trigger.

Internal clock trigger: Internally connected to direct trigger.

Clock recovery triggers (from optical sampling modules) - internally connected to pre-scaled trigger.

Trigger Sensitivity -

External direct trigger output:

50 mV, DC -4 GHz (typical).

100 mV, DC -3 GHz (guaranteed).

Pre-selected trigger input:

800 mV, 2 to 3 GHz (guaranteed).

600 mV, 3 to 10 GHz (guaranteed).

1000 mV, 10 to 12, 5 GHz (typical).

Jitter -

Short-term jitter optimized mode:

1.0 ps +5 ppm (typical).

≤1.5 ps +10 ppm (max.).

Locked to 10 MHz reference:

1.6 ps +0.05 ppm of position (typical).

≤2.5 ps +0.1 ppm of position (max.).

Internal Clock - Adjustable from 25 to 200 kHz (drives TDR, internal clock output and calibrator).

Trigger Level Range - ±1.0 V.

Trigger Input Range - ±1.5 V.

Trigger Holdoff - Adjustable 5 μs to 100 ms in 2 ns increments.

Display Features

Touchscreen Display - 10.4 in. diagonal, color.

Colors - 16,777,216 (24 bits).

Video Resolution - 640 horizontal by 480 vertical displayed pixels.

Math/Measurement System Measurements

The CSA8000 supports up to eight simultaneous measurements, updated three times per second with optional display of per measurement statistics (min, max, mean and standard deviation).

Measurement Set -

Amplitude Measurements: High, Low, Amplitude, Max, Mid, Min, Peak-to-peak, + Overshoot, - Overshoot, Mean, Cycle Mean, RMS, Cycle RMS, AC RMS, Gain.

Timing Measurements: Rise, Fall, Period, Frequency, + Cross,

- Cross, + Width, - Width, + Duty Cycle, - Duty Cycle, Burst Width, Delay, Phase.

Area Measurements: Area, Cycle Area.

Eye Pattern/Optical Measurements: Extinction Ratio (Ratio, %, dB), Eye Width, Eye Height, Crossing %, Duty Cycle Distortion, Jitter (p-p, RMS), Noise (p-p, RMS), Q-Factor, SNR, Average Optical Power.

Cursors - Dot, vertical bar and horizontal bar cursors.

Waveform Processing

Up to eight math waveforms can be defined and displayed using the following math functions: Add, Subtract, Multiply, Divide, Average, Differentiate, Exponentiate, Integrate, Natural Log, Log, Magnitude, Min, Max, Square Root and Filter.

In addition, measurement values can be utilized as scalars in math waveform definitions.

Mask Testing - In addition to user-defined masks, the following predefined masks are built-in:

| Standard | Rate (Mb/s) |
|-----------------------------|-------------|
| OC-1 | 51.84 |
| OC-3/STM-1 | 155.52 |
| OC-9 | 466.56 |
| OC-12/STM-4 | 622.08 |
| OC-18 | 933.12 |
| OC-24 | 1244.2 |
| OC-36 | 1866.2 |
| OC-48/STM-16 | 2488.3 |
| OC-192/STM-64* ¹ | 9953.3 |
| OC-768/STM-256 | 39813.12 |
| FEC 10.66 Gb/s | 10664.0 |
| FEC 42.66 Gb/s | 42656.0 |
| FC-133 | 132.81 |
| FC-266 | 265.6 |
| FC-531 | 531.2 |
| FC-1063 | 1062.5 |
| Gigabit Ethernet | 1250.0 |

*¹ OC192/STM-64 Mask is per ITU-T, 691 recommendation.

Power Requirements

Line-Voltage Ranges - 90 to 132 V_{RMS}, 180 to 250 V_{RMS}.

Line Frequency - 48 to 440 Hz.

Environmental

Temperature -

Operating: +10°C to +40°C.

Nonoperating: -22°C to +60°C.

Relative Humidity -

Operating: Floppy disk and CD-ROM not installed:
 20% to 80% at or below 40°C (upper limit derates to 45% relative humidity at 40°C).
 Nonoperating: 5% to 90% at or below 60°C (upper limit derates to 20% relative humidity at +60°C).

Altitude - Operating: 3,048 m (10,000 ft.); nonoperating: 12,190 m (40,000 ft.).

Electromagnetic Compatibility - 89/336/EEC.

Safety - UL3111-1, CSA1010.1, EN61010-1, IEC61010-1.

Physical Characteristics

| | Cabinet | Cabinet |
|-------------------|----------------|----------------|
| Dimensions | mm | in. |
| Width | 457 | 18.0 |
| Height | 343 | 13.5 |
| Depth | 419 | 16.5 |
| Weights | kg | lb. |
| Net | 20.8 | 46 |
| Shipping | 36.7 | 81 |

 [Top of Page](#)

[Features](#)

[> Specs](#)



Tektronix Measurement products are manufactured in ISO registered facilities.



85W-13499-3p1, 02/2000, 10/01/2001

[Have an Account Manager Contact Me](#)

[Request a Demo](#)

[Email This Page](#)


[Printable Page](#)

[URL for Favorites](#)

Tektronix Site

[Home](#) | [Products](#) | [Support](#) | [Buy](#) | [Contact Us](#) | [Investors](#) | [Careers](#) | [International](#) | [myTek](#)

[Sitemap](#) | [© Copyright Tektronix, Inc.](#) | [Privacy Statement](#)

 [Have an Account Manager Contact Me](#)

 [Request a Demo](#)

 [Email This Page](#)

 [Printable Page](#)

 [URL for Bookmarks](#)

Tektronix Site

[Home](#) | [Products](#) | [Support](#) | [Buy](#) | [Contact Us](#) | [Investors](#) | [Careers](#) | [International](#) | [myTek](#)

[Sitemap](#) | [© Copyright Tektronix, Inc.](#) | [Privacy Statement](#)