

# Specifications

## AQ8202-01 System Controller

Display	6.5-inch TFT color LCD
Serial interface	For AQ8202 connection: 4
GP-IB interface	IEEE-488.2 compatible
VGA interface	D-sub 15-pin
Power requirements	AC 100 to 120 ( $\pm 10\%$ )/200 to 240 ( $\pm 10\%$ ) V, 50/60 Hz, Max. 30 VA
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation) Overvoltage category: II, contamination level: 2, maximum altitude: 2000 m
Dimensions and mass	Approx. 425 (W) x 132.5 (H) x 110 (D) mm Approx. 4 kg
Accessories	Battery cable: 1 (with 3/2 terminal conversion plug), remote interlock short plug: 1, remote interlock connecting plug: 1, dust cover (for GP-IB connector: 1, for VGA connector: 1, for external expansion connector: 4), instruction manual: 1
Options	19-inch rack mount kit A (132.5)

## AQ8202 Expander Frame

Serial interface	For connection of AQ8202-01, AQ8203, AQ8204
Number of mountable modules	10
Power requirements	AC 100 to 120 ( $\pm 10\%$ )/200 to 240 ( $\pm 10\%$ ) V, 50/60 Hz, Max. 600 VA
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation) Overvoltage category: II, contamination level: 2, maximum altitude: 2000 m
Dimensions and mass	Approx. 425 (W) x 132.5 (H) x 500 (D) mm Approx. 10 kg
Accessories	Battery cable: 1 (with 3/2 terminal conversion plug), dust cover (for external expansion connector): 4, external expansion cable (1m): 1, instruction manual: 1
Options	AQ8202-901 Rack mount kit (for attaching AQ8202-01 Connection rack), AQ8202-903 Blank panel (19-inch EIA standard rack 3U blank panel), 19-inch rack mount kit A (132.5)

\*Calibration is required when mounting AQ8201-11\* and AQ8201-12\* you already use

## AQ8203 Halfsize Frame

Display	STN color LCD
Serial interface	For AQ8202 connection
GP-IB interface	IEEE-488.2 compatible
Number of mountable modules	3
Power requirements	AC 100 to 120 ( $\pm 10\%$ )/200 to 240 ( $\pm 10\%$ ) V, 50/60 Hz, Max. 190 VA
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation) Overvoltage category: II, contamination level: 2, maximum altitude: 2000 m
Dimensions and mass	Approx. 212 (W) x 132.5 (H) x 400 (D) mm Approx. 5.4 kg
Accessories	Battery cable: 1 (with 3/2 terminal conversion plug), remote interlock short plug: 1, remote interlock connecting plug: 1, optical output control key: 2, blank panel: 2, dust cover (for GP-IB connector: 1, for external expansion connector: 1), instruction manual: 1
Options	19-inch rack mount kit B (132.5) for connecting 2 units of AQ8203 19-inch rack mount kit C (132.5) for mounting 1 unit (left mount) of AQ8203 19-inch rack mount kit D (132.5) for mounting 1 unit (right mount) of AQ8203

## AQ8204 Frame Controller

Display	STN color LCD
Serial interface	For AQ8202 connection
GP-IB interface	IEEE-488.2 compatible
Number of mountable modules	8
Power requirements	AC 100 to 120 ( $\pm 10\%$ )/200 to 240 ( $\pm 10\%$ ) V, 50/60 Hz, Max. 600 VA
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation) Overvoltage category: II, contamination level: 2, maximum altitude: 2000 m
Dimensions and mass	Approx. 425 (W) x 132.5 (H) x 500 (D) mm Approx. 10 kg
Accessories	Battery cable: 1 (with 3/2 terminal conversion plug), remote interlock short plug: 1, remote interlock connecting plug: 1, optical output control key: 2, dust cover (for GP-IB connector: 1, for external expansion connector: 1), instruction manual: 1
Options	19-inch rack mount kit A (132.5)

## AQ8201-110 WDM DFB-LD Module (Light source)

Available wavelength range	1524.110 to 1620.500 nm <sup>1)</sup>	
Wavelength accuracy	±0.01 nm (typ.) <sup>2)</sup>	
Wavelength setting resolution	0.001 nm	
Spectral linewidth	NARROW	5 MHz or less <sup>3)</sup>
	WIDE	50 MHz (typ.) <sup>3)</sup>
Optical output level	+10 dBm or more <sup>2, 4)</sup>	
SMSR	45 dB (typ.) <sup>3)</sup>	
Output level stability	15 minutes	Within ±0.005 dB <sup>5)</sup>
	24 hours	Within ±0.03 dB <sup>5)</sup>
Wavelength stability	15 minutes	Within ±0.005 nm <sup>2)</sup>
	24 hours	Within ±0.01 nm <sup>2)</sup>
Wavelength range	1.6 nm or more <sup>2)</sup>	
Optical attenuation range	10 dB (0.01 dB step)	
Optical isolation	55 dB (typ.)	
RIN	-145 dB/Hz (typ.) <sup>3)</sup>	
Internal modulation	100 Hz to 300 kHz (CHOP)	
Applicable fiber	SM (9/125 μm)	
Optical connector	FC/Angled PC <sup>6)</sup>	
Laser product safety class	IEC60825-1: class3A, 21CFR1040.10: class IIIb <sup>7)</sup>	
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation)	
Dimensions and mass	Approx. 39.5 (W) x 130 (H) x 339 (D) mm Approx. 0.7 kg	

\*Specifications assured at fixed temperature within 25±3 °C

\*Specifications assured after warm-up for one hour

Notes:

1) Select from AQ8201-110 available wavelength.

2) Ambient temperature: 25±3 °C (at constant temperature), CW light, attenuation 0.0 dB, central wavelength, at fiber end (FC/Angled PC-FC/SPC, 2 m, SMF), spectral linewidth: NARROW

3) CW light, attenuation 0.0 dB, central wavelength

4) Using master cord

5) Ambient temperature: 25±3 °C (at constant temperature), CW light, attenuation 0.0 dB, central wavelength, at fiber end (FC/Angled PC-FC/SPC, 2 m, SMF), spectral linewidth: WIDE

6) Angled PC manufactured by SEIKOH GIKEN or equivalent (step type)

7) Label examples

Laser product safety class label



### • Option 01 (for high output level)

Optical output level	+13 dBm or more
----------------------	-----------------

Note: Ambient temperature: 25±3 °C, CW light, attenuation 0.0 dB, central wavelength, at fiber end (FC/Angled PC-FC/SPC, 2 m, SMF or PMF), spectral linewidth: NARROW, using master cord

### • Option 02 (for PMF)

Applicable fiber	PM (9/125 μm)
Polarization extinction ratio	20 dB or more <sup>Note</sup>

Note: CW light, attenuation 0.0 dB, central wavelength, spectral linewidth: NARROW, assured at the end of the optical connector mounted on the panel

### • Option 03 External modulation (for sine waveform)

External modulation	100 Hz to 300 kHz
Input connector	SMA

Note: Cannot use Option 03 and Option 04 simultaneously

### • Option 04 External modulation (for CHOP)

External modulation	100 Hz to 300 kHz
Input connector	SMA

Note: Cannot use Option 04 and Option 03 simultaneously

\*Option 01 – 04 can be specified only in case of new order; unless specifically noted, options can be used simultaneously

## AQ8201-12, 12A ASE Module (Light source)

Spectrum density (-13 dBm/nm)	1525 to 1570 nm (typ.) <sup>1)</sup> 1530 to 1565 nm <sup>1)</sup>	
Total output power	+10 dBm or more <sup>1, 2)</sup> (AQ8201-12) +15 dBm or more <sup>1, 2)</sup> (AQ8201-12A)	
Output level stability	5 minutes	±0.005 dB (typ.) <sup>1, 3)</sup>
	1 hour	Within ±0.05 dB <sup>1, 4)</sup>
Optical modulation mode	CW	
Polarization extinction ratio	0.1 dB (typ.)	
Optical attenuation range	6 dB (0.1 dB step)	
Applicable fiber	SM (9/125 μm)	
Optical connector	AQ9441 (*) Universal Adapter (option) <sup>5)</sup>	
Laser product safety class	IEC60825-1: class 3A 21CFR1040.10: class IIIb <sup>6)</sup>	
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation)	
Dimensions and mass	Approx. 79.5 (W) x 130 (H) x 339 (D) mm Approx. 1.3 kg	

\*Specifications assured at fixed temperature within 25±3 °C

\*Specifications assured after warm-up for one hour

Notes:

1) CW light, attenuation 0.0 dB, at SM fiber end (both end FC/PC, 2 m)

2) Using master cord

3) 5 minutes (at constant temperature in 20 to 30 °C)

4) One hour (at a temperature in 5 to 40 °C)

5) Specify FC, SC or ST.

6) Label examples

Laser product safety class label



## AQ8201-13/13B ECL Module (Light source)

Model	AQ8201-13		AQ8201-13B	
Available wavelength range	1460 to 1580 nm		1500 to 1620 nm	
Wavelength setting resolution	10 pm			
Wavelength accuracy	Within $\pm 0.2$ nm <sup>1, 2, 3, 4)</sup>			
Wavelength repeatability	$\pm 50$ pm (typ.) <sup>1, 2, 4)</sup>			
Wavelength setting time	3 seconds (typ.) <sup>5)</sup>			
Spectral linewidth	NARROW	5 MHz (typ.) <sup>1, 2)</sup>		
	WIDE	100 MHz (typ.) <sup>1, 2)</sup>		
Optical output level	1460 to 1580 nm	+6 dBm or more <sup>1, 2, 6)</sup>		
	1490 to 1580 nm	+8 dBm or more <sup>1, 2, 6)</sup>		
	1520 to 1580 nm	+10 dBm or more <sup>1, 2, 6)</sup>		
	1500 to 1620 nm	+6 dBm (typ.) <sup>1, 2, 6)</sup>		
	1530 to 1620 nm	+8 dBm (typ.) <sup>1, 2, 6)</sup>		
	1560 to 1620 nm	+10 dBm (typ.) <sup>1, 2, 6)</sup>		
SMSR	45 dB or more <sup>1, 2, 7)</sup>			
Output level stability	15 minutes	Within $\pm 0.005$ dB <sup>1, 2, 4, 8)</sup>		
	1 hour	Within $\pm 0.01$ dB <sup>1, 2, 4, 8)</sup>		
Wavelength stability	15 minutes	Within $\pm 0.005$ nm <sup>1, 2, 4)</sup>		
	24 hours	$\pm 0.01$ nm (typ.) <sup>1, 2, 4)</sup>		
Optical attenuation range	10 dB (0.01 dB step) <sup>1, 7)</sup>			
RIN	-145 dB/Hz (typ.) <sup>1, 2)</sup>			
External modulation	100 Hz to 300 kHz (Sine Wave)			
Applicable fiber	SM (9/125 $\mu$ m)			
Optical connector	FC/Angled PC <sup>9)</sup>			
Laser product safety class	IEC60825-1: class3A 21CFR1040.10: class IIIb <sup>10)</sup>			
Environmental conditions	Operation temperature: $23 \pm 5$ °C <sup>11)</sup> Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation)			
Dimensions and mass	Approx. 39.5 (W) x 130 (H) x 339 (D) mm Approx. 1.2 kg			

\*Specifications assured after warm-up for one hour

Notes:

- 1) Temperature fixed at 23 °C, CW light, 2 m fiber output, single vertical mode
- 2) Optical attenuation: 0.00 dB
- 3) After wavelength calibration
- 4) AQ8201-13: 1520 to 1570 nm, AQ8201-13B: 1560 to 1610 nm
- 5) Full span (120 nm)
- 6) Using master cord
- 7) AQ8201-13: wavelength: 1550 nm, AQ8201-13B: wavelength: 1580 nm
- 8) Spectrum linewidth: WIDE
- 9) Angled PC manufactured by SEIKOH GIKEN or equivalent (step type)
- 10) Label examples

Laser product safety class label



11) Ambient temperature of mainframe

## AQ8201-13A/13D ECL Module (Light source supports PMF)


Model	AQ8201-13A		AQ8201-13D	
Available wavelength range	1460 to 1580 nm		1500 to 1620 nm	
Wavelength setting resolution	10 pm			
Wavelength accuracy	Within $\pm 0.2$ nm <sup>1, 2, 3, 4)</sup>			
Wavelength repeatability	$\pm 50$ pm (typ.) <sup>1, 2, 4)</sup>			
Wavelength setting time	3 seconds (typ.) <sup>5)</sup>			
Spectral linewidth	NARROW	5 MHz (typ.) <sup>1, 2)</sup>		
	WIDE	100 MHz (typ.) <sup>1, 2)</sup>		
Optical output level	1460 to 1580 nm	+5 dBm or more <sup>1, 2, 6)</sup>		
	1490 to 1580 nm	+7 dBm or more <sup>1, 2, 6)</sup>		
	1520 to 1580 nm	+9 dBm (typ.) <sup>1, 2, 6)</sup>		
	1500 to 1620 nm	+5 dBm (typ.) <sup>1, 2, 6)</sup>		
	1530 to 1620 nm	+7 dBm (typ.) <sup>1, 2, 6)</sup>		
	1560 to 1620 nm	+9 dBm (typ.) <sup>1, 2, 6)</sup>		
SMSR	45 dB or more <sup>1, 2, 7)</sup>			
Output level stability	15 minutes	Within $\pm 0.005$ dB <sup>1, 2, 4, 8)</sup>		
	1 hour	Within $\pm 0.01$ dB <sup>1, 2, 4, 8)</sup>		
Wavelength stability	15 minutes	Within $\pm 0.005$ nm <sup>1, 2, 4)</sup>		
	24 hours	$\pm 0.01$ nm (typ.) <sup>1, 2, 4)</sup>		
Optical attenuation range	10 dB (0.01 dB step) <sup>1, 7)</sup>			
RIN	-145 dB/Hz (typ.) <sup>1, 2)</sup>			
External modulation	100 Hz to 300 kHz (Sine Wave)			
Polarization extinction ratio	20 dB (typ.) <sup>9)</sup>			
Applicable fiber	PM (9/125 $\mu$ m)			
Optical connector	FC/Angled PC <sup>10)</sup>			
Laser product safety class	IEC60825-1: class3A 21CFR1040.10: class IIIb <sup>11)</sup>			
Environmental conditions	Operation temperature: 5 to 40 °C <sup>12)</sup> Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation)			
Dimensions and mass	Approx. 39.5 (W) x 130 (H) x 339 (D) mm Approx. 1.2 kg			

\*Specifications assured after warm-up for one hour

Notes:

- 1) Temperature fixed at 23 °C, CW light, 2 m fiber output, single vertical mode
- 2) Optical attenuation: 0.00 dB
- 3) After wavelength calibration
- 4) AQ8201-13A: 1520 to 1570 nm, AQ8201-13D: 1560 to 1610 nm
- 5) Full span (120 nm)
- 6) Using master cord
- 7) AQ8201-13A: wavelength: 1550 nm, AQ8201-13D: wavelength: 1580 nm
- 8) Spectrum linewidth: WIDE
- 9) At the end of the optical connector mounted on the panel (CW light, attenuation 0.0 dB, wavelength: 1550 nm)
- 10) Angled PC manufactured by SEIKOH GIKEN or equivalent (step type)
- 11) Label examples

Laser product safety class label



## AQ8201-21 OPM Module (Optical powermeter)

Wavelength range	700 to 1700 nm	
Photodetector	Cooled InGaAs	
Application	Small-diameter silica fiber emission <sup>1)</sup>	
Optical connector	AQ9389B (FC) Connector Adapter: standard <sup>2)</sup>	
Polarization dependent loss	0.02 dB <sub>P-P</sub> (typ.) <sup>3)</sup>	
Power range	CW light	-80 to +27 dBm <sup>4)</sup>
	Chopped light	-80 to +24 dBm <sup>4)</sup>
Inaccuracy under reference condition	±2.5 % (at 1310 nm calibration point) <sup>5)</sup>	
Total accuracy	±5 % (1000 to 1650 nm) <sup>6)</sup>	
Linearity	±0.05 dB (1000 to 1650 nm, -40 to +27 dBm) <sup>7)</sup>	
Noise	CW light	-73 dBm or less <sup>8)</sup>
	Chopped light	
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation)	
Dimensions and mass	Approx. 39.5 (W) x 130 (H) x 339 (D) mm Approx. 0.8 kg	
Accessories	Plug for analogue output	

\*Specifications assured at fixed temperature within 23±5 °C

\*Specifications assured after warm-up for one hour

Notes:

- 1) Applicable fiber  $\leq 62.5/125 \mu\text{m}$  (GI), NA  $\leq 0.275$
- 2) ST and SC connector are also available
- 3) At 1550 nm wavelength, SM fiber
- 4) At 1310 nm wavelength
- 5) Reference conditions:
  1. Power level: -20 dBm (10  $\mu\text{W}$ ), CW light
  2. SM fiber, master FC connector
  3. Ambient temperature: 23±5 °C
  4. Calibrated with AQ9389B (FC) connector adapter (If you disconnect connector adapter, the accuracy of specifications may be lost. When you change connector adapter, we recommend you to have recalibration.)
- 6) Operation conditions:
  1. Power level: -20 dBm (10  $\mu\text{W}$ ), CW light
  2.  $\leq 50 \mu\text{m}$  optical fiber, NA  $\leq 0.2$
  3. Ambient temperature: 23±5 °C
  4. With AQ9389B (FC) connector adapter
- 7) 1. Linearity at a wavelength within wavelength specified in total accuracy  
2. CW light, ambient temperature: 23±5 °C
- 8) 1. Averaging 1s (averaging executed 10 times)  
2. In wavelength 1200 to 1600 nm  
3. CW, chopped light (270 Hz)

## AQ8201-22 DUAL OPM Module (Optical powermeter)

Wavelength range	1280 to 1700 nm
Photodetector	InGaAs
Application	Small-diameter silica fiber emission <sup>1)</sup>
Optical connector	AQ9389B (FC) Connector Adapter (standard) <sup>2)</sup>
Polarization dependent loss	0.02 dB <sub>P-P</sub> (typ.) <sup>3)</sup>
Power range (CW light)	-80 to +10 dBm <sup>3)</sup>
Inaccuracy under reference condition	±2.5 % (at 1550 nm calibration point) <sup>4)</sup>
Total accuracy	±5 % (1470 to 1610 nm) <sup>6)</sup>
Linearity	±0.05 dB (1470 to 1610 nm, -73 to +10 dBm) <sup>6)</sup>
Noise (CW light)	-73 dBm or less <sup>7)</sup>
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation)
Dimensions and mass	Approx. 39.5 (W) x 130 (H) x 339 (D) mm Approx. 1.2 kg

\*Specifications assured at fixed temperature within 23±1 °C

\*Specifications assured after warm-up for one hour

Notes:

- 1) Applicable fiber  $\leq 9/125 \mu\text{m}$  (SM), NA  $\leq 0.1$
- 2) ST and SC connector are also available
- 3) At 1550 nm wavelength, SM fiber
- 4) Reference conditions:
  1. Power level: 0 dBm, CW light
  2. SM fiber, master FC connector NA  $\leq 0.1$
  3. Calibrated with AQ9389B (FC) connector adapter (If you disconnect connector adapter, the accuracy of specifications may be lost. When you change connector adapter, we recommend recalibration.)
- 5) Operation conditions:
  1. Power level: 0 dBm, CW light
  2. SM fiber, FC connector NA  $\leq 0.1$
- 6) 1. Linearity at a wavelength within wavelength specified in total accuracy.
- 7) 1. Averaging 1s (averaging executed 10 times)  
2. In wavelength 1470 to 1610 nm
3. CW light

## AQ8201-32 ATTN Module (Optical attenuator)

Wavelength range	1200 to 1600 nm
Insertion loss	2.5 dB or less (1310/1550 nm) <sup>1,2)</sup>
Maximum attenuation level	60 dB
Attenuation deviation	Within ±0.1 dB (1310/1550 nm) <sup>1,2)</sup>
Repeatability	Within ±0.02 dB <sup>1)</sup>
Minimum attenuation step	0.01 dB
Optical return loss	60 dB or more (1310/1550 nm) <sup>1,2,3)</sup>
Polarization dependent loss	0.05 dB <sub>P-P</sub> (typ.) (1550 nm) <sup>1)</sup>
Maximum input power	+23 dBm
Shutter isolation	100 dB or more
Applicable fiber	SM (9/125 $\mu\text{m}$ )
Optical connector	FC/Angled PC <sup>4)</sup>
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation)
Dimensions and mass	Approx. 39.5 (W) x 130 (H) x 339 (D) mm Approx. 1 kg

\*Specifications assured at fixed temperature within 25±3 °C.

\*Specifications assured after warm-up for one hour.

Notes:

- 1) At constant temperature
- 2) Using master cord
- 3) With FC/Angled PC connector (Return loss: 63 dB or more)
- 4) Angled PC manufactured by SEIKOH GIKEN or equivalent (step type)

## AQ8201-32A, 33 ATTN Module (Supports L-band)

Wavelength range	1480 to 1650 nm
Insertion loss	2.5 dB or less (1550 nm) <sup>1,2)</sup>
Maximum attenuation level	60 dB
Attenuation deviation	Within ±0.1 dB (1520 to 1620 nm) <sup>1,2,3)</sup>
Repeatability	±0.01 dB (typ.) (AQ8201-32A)
	±0.005 dB (typ.) (AQ8201-33)
Minimum attenuation step	0.01 dB (AQ8201-32A)
	0.001 dB (AQ8201-33)
Optical return loss	60 dB or more (1550 nm) <sup>1,2,4)</sup>
Polarization dependent loss	0.05 dB <sub>P-P</sub> (typ.) (1550 nm) <sup>1)</sup>
Maximum input power	+23 dBm
Shutter isolation	100 dB or more
Applicable fiber	SM (9/125 $\mu\text{m}$ )
Optical connector	FC/Angled PC <sup>5)</sup>
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation)
Dimensions and mass	Approx. 39.5 (W) x 130 (H) x 339 (D) mm Approx. 1 kg

\*Specifications assured at fixed temperature within 25 °C.

\*Specifications assured after warm-up for one hour

Notes:

- 1) At constant temperature
- 2) Using master cord
- 3) Except polarization dependent loss
- 4) With FC/Angled PC connector (Return loss: 63 dB or more)
- 5) Angled PC manufactured by SEIKOH GIKEN or reference product (step type)

## AQ8201-33M ATTN Module (With monitor port)

Wavelength range	1480 to 1650 nm
Insertion loss	4.0 dB or less (1550 nm) <sup>1,2)</sup>
Maximum attenuation level	60 dB
Attenuation deviation	Within $\pm 0.1$ dB (1520 to 1620 nm) <sup>1, 2, 3)</sup>
Repeatability	$\pm 0.01$ dB (typ.) <sup>1)</sup>
Minimum attenuation step	0.001 dB
Optical return loss	50 dB or more (1550 nm) <sup>1, 2, 4)</sup>
Polarization dependent loss	0.1 dB <sub>P-P</sub> (typ.) (1550 nm) <sup>1)</sup>
Maximum input power	+23 dBm
Monitor output	10 dB (typ.) <sup>5)</sup>
Shutter isolation	100 dB or more
Applicable fiber	SM (9/125 $\mu$ m)
Optical connector	FC/Angled PC <sup>6)</sup>
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation)
Dimensions and mass	Approx. 39.5 (W) x 130 (H) x 339 (D) mm Approx. 1 kg

\*Specifications assured at fixed temperature within 25 °C

\*Specifications assured after warm-up for one hour

Notes:

- 1) At constant temperature
- 2) Using master cord
- 3) Except polarization dependent loss
- 4) With FC/Angled PC connector (Return loss: 63 dB or more)
- 5) To output port
- 6) Angled PC manufactured by SEIKOH GIKEN or equivalent (step type)

## AQ8201-412/-422 DUAL OSW Module

Number of channels	1 x 2 (AQ8201-412) 2 x 2 (AQ8201-422)
Wavelength range	1480 to 1620 nm
Insertion loss	1.7 dB or less <sup>1)</sup>
Optical return loss	50 dB or more <sup>1)</sup>
Optical isolation	60 dB or more <sup>1)</sup>
Polarization dependent loss	0.05 dB <sub>P-P</sub> (typ.) <sup>1)</sup>
Repeatability	$\pm 0.02$ dB (typ.) <sup>1, 2)</sup>
Applicable fiber	SM (9/125 $\mu$ m)
Optical connector	FC/Angled PC <sup>3)</sup>
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation)
Dimensions and mass	Approx. 39.5 (W) x 130 (H) x 339 (D) mm Approx. 0.6 kg (AQ8201-412) Approx. 39.5 (W) x 130 (H) x 339 (D) mm Approx. 0.7 kg (AQ8201-422)

\*Specifications assured at fixed temperature within 25 $\pm$ 3 °C

Notes:

- 1) At constant temperature, using master cord including connector, at 1550 nm wavelength
- 2) After warm-up for one hour
- 6) Angled PC manufactured by SEIKOH GIKEN or equivalent (step type)

## AQ8201-414/-418/-43 OSW Module

Number of channels	1 x 4 (AQ8201-414) 1 x 8 (AQ8201-418) 1 x 12 (AQ8201-43)
Wavelength range	1480 to 1620 nm
Insertion loss	1.5 dB or less <sup>1)</sup>
Optical return loss	55 dB or more <sup>1)</sup>
Optical isolation	70 dB or more <sup>1)</sup>
Polarization dependent loss	0.05 dB <sub>P-P</sub> (typ.) <sup>1)</sup>
Repeatability	$\pm 0.02$ dB (typ.) <sup>1, 2)</sup>
Applicable fiber	SM (9/125 $\mu$ m)
Optical connector	FC/Angled PC <sup>3)</sup>
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation)
Dimensions and mass	Approx. 39.5 (W) x 130 (H) x 339 (D) mm Approx. 0.6 kg (AQ8201-414) Approx. 39.5 (W) x 130 (H) x 339 (D) mm Approx. 0.7 kg (AQ8201-418) Approx. 79.5 (W) x 130 (H) x 339 (D) mm Approx. 1.0 kg (AQ8201-43)

\*Specifications assured at fixed temperature within 25 $\pm$ 3 °C

Notes:

- 1) At constant temperature, using master cord including connector, at 1550 nm wavelength
- 2) After warm-up for one hour
- 6) Angled PC manufactured by SEIKOH GIKEN or equivalent (step type)

## AQ8201-71 RLM Module (Return loss measurement)

Wavelength range	1280 to 1620 nm
Dynamic range	65 dB or more <sup>1)</sup>
Relative measurement accuracy	Within $\pm 0.4$ dB (0 to 50 dB) <sup>2)</sup> Within $\pm 0.7$ dB (50 to 60 dB) <sup>2)</sup>
Measurement stability	Within $\pm 0.02$ dB <sup>3)</sup>
Applicable fiber	SM (9/125 $\mu$ m)
Input connector (from light source)	FC/PC
Output connector(to DUT)	SC/Angled PC <sup>4, 5)</sup>
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation)
Dimensions and mass	Approx. 39.5 (W) x 130 (H) x 339 (D) mm Approx. 1.2 kg
Options	Master cord (FC), (SC) and (Open) for AQ8201-71

\*Specifications assured after warm-up for one hour

**General conditions other than specified:**

- Optical input level: -5 to 0 dBm, CHOP (270 Hz)
- Wavelength: 1550 nm
- Reference: Fresnel reflection (using master cord for AQ8201-71)
- Ambient temperature: 23 $\pm$ 1 °C

Notes:

- 1) Varies depending on master cord
- 2) Depends on stability of light source used, linearity of photo receiver and isolation of optical directional coupler
- 3) Display stability with Fresnel reflection measurement: 5 minutes
- 4) Angled PC manufactured by SEIKOH GIKEN or equivalent (step type)
- 5) Do not connect other master cord than that specified by ANDO to output connector

## AQ8201-818 SPLTR/CPLR Module

Wavelength range	1480 to 1620 nm
Insertion loss (All ports)	12.5 dB or less <sup>1)</sup>
Directivity	45 dB or more <sup>1)</sup>
Polarization dependent loss	0.2 dB <sub>P-P</sub> (typ.) <sup>1)</sup>
Applicable fiber	SM (9/125 μm)
Optical connector	FC/Angled PC <sup>2)</sup>
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation)
Dimensions and mass	Approx. 39.5 (W) x 130 (H) x 339 (D) mm Approx. 0.6 kg

\*Specifications assured at fixed temperature within 25±3 °C

Notes:

- 1) At constant temperature, using master cord including connector, at 1550 nm wavelength
- 2) Angled PC manufactured by SEIKOH GIKEN or equivalent (step type)

## AQ8201-855 3 x SPLTR/CPLR Module

Wavelength range	1480 to 1620 nm
Insertion loss (All ports)	4.5 dB or less <sup>1)</sup>
Directivity	50 dB or more <sup>1)</sup>
Polarization dependent loss	0.1 dB <sub>P-P</sub> (typ.) <sup>1)</sup>
Applicable fiber	SM (9/125 μm)
Optical connector	FC/Angled PC <sup>2)</sup>
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation)
Dimensions and mass	Approx. 39.5 (W) x 130 (H) x 339 (D) mm Approx. 0.6 kg

\*Specifications assured at fixed temperature within 25±3°C

Notes:

- 1) At constant temperature, using master cord including connector, at 1550 nm wavelength
- 2) Angled PC manufactured by SEIKOH GIKEN or equivalent (step type)

## AQ8201-873 3 x SPLTR/CPLR Module

Wavelength range	1480 to 1620 nm
Insertion loss (70 % ports)	3.0 dB or less <sup>1)</sup>
Insertion loss (30 % ports)	7.0 dB or less <sup>1)</sup>
Directivity	50 dB or more <sup>1)</sup>
Polarization dependent loss	0.1 dB <sub>P-P</sub> (typ.) <sup>1)</sup>
Applicable fiber	SM (9/125 μm)
Optical connector	FC/Angled PC <sup>2)</sup>
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation)
Dimensions and mass	Approx. 39.5 (W) x 130 (H) x 339 (D) mm Approx. 0.6 kg

\*Specifications assured at fixed temperature within 25±3 °C

Notes:

- 1) At constant temperature, using master cord including connector, at 1550 nm wavelength
- 2) Angled PC manufactured by SEIKOH GIKEN or equivalent (step type)

## AQ8201-891 3 x SPLTR/CPLR Module

Wavelength range	1480 to 1620 nm
Insertion loss (90 % ports)	1.5 dB or less <sup>1)</sup>
Insertion loss (10 % ports)	12.5 dB or less <sup>1)</sup>
Directivity	50 dB or more <sup>1)</sup>
Polarization dependent loss	0.1 dB <sub>P-P</sub> (typ.) <sup>1)</sup>
Applicable fiber	SM (9/125 μm)
Optical connector	FC/Angled PC <sup>2)</sup>
Environmental conditions	Operation temperature: 5 to 40 °C Storage temperature: 0 to 50 °C Humidity: 85 % RH or less (no condensation)
Dimensions and mass	Approx. 39.5 (W) x 130 (H) x 339 (D) mm Approx. 0.6 kg

\*Specifications assured at fixed temperature within 25±3 °C

Notes:

- 1) At constant temperature, using master cord including connector, at 1550 nm wavelength
- 2) Angled PC manufactured by SEIKOH GIKEN or equivalent (step type)